

DRIVER FEEDBACK SIGNS

IQ1200 Portable Driver Feedback Sign



Part #: M75-12DFB-PK0x

The IQ1200 Series of Radar Driver Feedback Signs offers solutions for increasing driver speed awareness and road safety. The bright 12" characters can be seen from up to 600' away, and help increase driver speed awareness on neighborhood streets where so many small accidents occur every year. SafetyCalm data collection software allows you to gather hard data of traffic patterns and program the sign to help keep streets safer. The IQ1200 Portable Driver Feedback Sign offers multi-site versatility.

Temporarily deploy the lightweight sign to locations of your choice with the ease of our two-bolt mounting system.

Individual mounting brackets are available as an accessory, and one is required per location.

TraffiCalm™ Driver Feedback Signs are manufactured in the USA in an ISO 9001:2015 certified facility, meeting and exceeding industry standards and state testing

requirements. TraffiCalm™ signs are unmatched in durability, accuracy, ease of use and affordability.

Features:

- Bluetooth wireless programming
- SafetyCalm Configuration and Traffic Data Collection software and Android App included free
- Emoticon display options to increase driver awareness
- Programmable full matrix display allows the sign to display speed numbers as well as messages like 'SLOW DOWN'.
- 100% MUTCD compliant
- Built in 30Ah battery pack and Smart AC charger for charging between deployments
- K-band (24.15GHz) radar, range 450+ feet.
- Unlimited tech support and customer service from our USA facility for the life of the sign
- Fast delivery- typically ships within 2 weeks of order
- 3 year limited warranty



Package Includes:


Driver Feedback sign, mounting bracket, Smart AC charger, SafetyCalm™ Configuration and Traffic Data Collection Software, installation and user manual.

Why TraffiCalm™?

- ISO 9001:2015 Certified USA based facility
- All signs 100% MUTCD compliant
- Vandal resistant designs
- Broadest range of sizes and options in the industry
- Industry leading turnaround from order to delivery
- Unlimited tech support and customer service from our USA facility
- Industry Pioneers in Enhanced Road Signage

SafetyCalm

SafetyCalm Configuration and Traffic Data Collection Software allows you to program your sign from your laptop and collect and graphically display traffic data



TRAFFICALM
SYSTEMS

Feature	Specifications
LED and Radar Components	
Speed Display Height	12" high numbers
Text & Emoticon Height	5" high two lines 'SLOW DOWN' text; 12" high 'smile' or 'sad' face emoticon
"YOUR SPEED" Legend	4" high highway gothic font (MUTCD compliant)
LED, 1/2 Cone Angle	Amber (590nm); 1/2 Angle 15°; Rated 100,000 hours; 20,000 CDA/ M^2, Auto Dimming employed
Amber LED on Axis Intensity	20,000 CDA/SQ meter
Sign Legibility	Viewable range: 750 feet; legible range: 600 feet
Speed Resolution and Range	Min 5 mph; Max 143 mph in 1 mph steps (min 8 kph, max 230 kph in 1.6 kph steps)
Radar Specification and Range	K-band (24.15GHz) direct sensing; license free (FCC part 15 compliant); average range at 450 feet (plus 400' or minus 100' depending on vehicle size)
Materials and Construction	
Chassis Size/Total Weight	24" width x 30" height x 2-1/4" depth; under 28 pounds with bracket
Front Face Sheeting	3M™ Diamond Grade™, high visibility prismatic, long life protective sheeting
Sign Face Color	White; fluorescent yellow-green; with additional colors optional
Sign Mounting Construction	1/8" thick aluminum brackets and face; standard 3% tilt bracket configuration; flat mount brackets optional
Vandal Resistant Construction	Sealed electronics box (ECS) 1/16" thick aluminum enclosure attached to a 1/8" thick mounting plate.
	3/16" high impact polycarbonate face with high contrast mask; anti-glare graffiti and sunlight resistant
	Provisions for padlocking in place are provided
	Standard DOT powder coat green color with additional colors optional
Electronics Enclosure Rating	Weatherproof; NEMA 3R
Electrical Specifications	
Power Requirements	2W stealth; 300MW standby; 6W night; 28W day
Voltage Requirements	9V-30VDC; 12VDC Nominal (Battery protection at 11.5VDC and 10.8VDC; startup at 12.3VDC)
Power Options	Indoor rated AC charging adapter included
Operating Temperature	Internal components: -34°C to +74°C/-29°F to +165°F
	Ambient environment: -34°C to +60°C/-29°F to 140°F
Warranties	3 year limited warranty.
SafetyCalm™ Configuration and Traffic Data Collection Software	
Data Collection	SafetyCalm™ software, license free
Event Logging with Time Stamp	Event data: 60 days with a circular buffer; applied voltage (VDC); internal temperature (°C); ambient light (lux); display functional status; traffic status; shock sensor events; parameter events
Vehicle Data Logging Capacity	Speed Data: 90 days with circular buffer (oldest reading replaced by newest) based on 24/7 operation
Programmable Display Features	Min. speed limit; speed limit; over speed; and maximum speed to display
	Display type: blank (stealth mode); actual speed; speed limit; flashing digits; steady digits; strobing digits and strobing 'SLOW DOWN' text
	Programmable integrated "SLOW DOWN" Message; external beacon control
Schedules	Repeating daily: 9 events; repeating weekly: 9 events; non-repeating dated: 9 events; (27 events in one 24 hour period; 365 days per year while powered)
Communications	Bluetooth Class 1 connectivity (V2.1 +EDC) min at 30' (FCC certified); RS232 port
	Android App available on play store free of charge
System Requirements	Operating system: Windows XP, Windows Vista, Windows 7; Windows 10
	Screen resolution: 1024 x 768 or better
	Communications interfaces: Bluetooth Class 1 or 2 adapters (capabilities: V1.0, V1.2, V2.0, V2.1 + EDC)
	Disk space: 16.5MB minimum

released: 20210113

